AHD IR SPEED DOME

Key feature:

* Keep original analog system
* Coaxial transmission and control
* Real time transmission,lossless video
* High definition 720P / 33X Zoom
* Long distance transmission up to 500 meters
* OSD menu available / IR distance 150M
* 7" Total Metal body construction, IP66 rate protection
* IR illumination & power consumption is variable dependant on zoom factor

Specification

Camera	
Sensor	1/3" progressive scan CMOS
Effective pixels	720P(1280X720)
Total pixels	1.3MP
Lens	33X optical zoom
Focus Distance	4.6mm~152mm
Iris	F1.6 ~F2.8
View of Angle	H：54.8°（W）～3.4°（T） V：41°（W）～2.5°（T）
Min. illumination	Color: 0.1 Lux \ B/W: 0.01Lux
D/N	IR-CUT
S/N Ratio	≥50dB
Dome	
Pan range	360°continuous rotation
Tilt range	0°~93° auto flip 180°
Manual Pan speed	0.02~300°/S
Manual Tilt speed	0.02~160°/S
Preset Points	220
Pattern Scan	4 groups
Guard Tours	4 groups
Guard Points	Max.16 points, dwell time user selectable
Operating temperature	Outdoor: -40°~ +60°
Operation menu	English
Pan and Tilt position display	Support
Humidity	≤95% Non Condensing
Power	AC24V
Consumption	< 25W
Lightning Protection	Transient voltage 6000V
Video interface output	AHD
Communication mode	RS485 (+/-)/ Coaxial Cable

Connection	Coaxial Cable
Related validation	IP66,CE,FCC,RoHs
IR parameters	
Auto Control IR LED	PWM
LEDs	42Mil 10pcs
IR distance	Up to 150 meters
Support ambient light detection	IR illumination on 1-25 grades selectable;