

	
SPECIFICATION	
Model NO.	L360-5MIPC ER3
Camera 360 degree	
Image Sensor	1/2.9" SONY Low Illumination CMOS Sensor
Resolution	4MP
Effective Pixels	3096 (H) × 2202 (V)
Compression	H.264/H.265/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network, cvbs
Reset Button	YES
LENS Type	
Focus Length	Board Lens 1.05mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	5MP
Night Vision	
Infrared LED	42μx 3PCS
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS, RTP,RTSP,RTCP, NTP,SMTP

L360-5MIPCA

ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Internal POE, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	2048*2048@15fps
Main Stream 2	1520*1520@20fps
Main Stream 3	1024*1024@20fps
Sub Stream 1	720*720@15fps 720*720@20fps
Tri Stream	512*512@15fps 512*512@20fps
IE Brower	IE9-11, Google Chrome(Under Ver 45), Firefox(Under Ver 53), Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Defog Mode	Support
BLC	Support
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/VMS/Web/SD Card
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands, Czech
Interface	
Audio	2-way audio(3.5mm audio interface)
Alarm	1channel Input/Ouput
SD Card Slot	support 128G Micro SD With External SD Card Slot
General	
Housing	Body:Metal, Bracket: Plastic
Anti-cut Bracket	NO
IR Cut Filter	YES
Operation Temperature	-20℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 950mA
Dimension	∅ 120 x 49(H) mm
Weight	500g