

RMH Series

RMH-1628EU-N / RMH-1628AU-N / RMH-1628AU-B

16 CH AHD+TVI standalone DVR*N housing***1080P****Support
960H***B housing*

Main Features

- 16 CH video inputs
- Recording frame rate per channel
1080P@15/12fps
720P & 960H@30/25fps
- 16 CH sync real-time playback
- Auto signal detection
- Multiple input: mix any signal
on same screen
- All in one solution: supports AHD,
TVI and analog 960H & D1
- RS-485 serial interface
- Touch panel LCD monitor supported



**Display different sources
on the same screen,
no setting needed**

Model		RMH-1628EU-N	RMH-1628AU-N	RMH-1628AU-B
Camera Input		16CH AHD & TVI Universal		
Housing		N		B
Video	Input	TVI: 1080P @ 30/25 fps, 720P @ 60/50 fps, 720P @ 30/25 fps AHD: 1080P @ 30/25 fps, 720P @ 60/50 fps, 720P @ 30/25 fps 960H / D1		
	Output	1 HDMI with Audio and 1 VGA (Max. 1920x1080)		
Audio	Input	1 RCA	8 RCA	
	Output	1 RCA	2 RCA	
System	Operating System	Embedded Linux OS		
	SATA Devices	Max. 2 x SATA Devices (HDDx2, HDDx1+ Optical Device x1)	Max. 4 x SATA Devices (HDDx3+eSATAx1, HDDx2+ Optical Device x1+eSATAx1)	Supports Max. x 7 SATA Devices (HDDx6+eSATAx1, HDDx4+ Optical Device x1+eSATAx1)
	External HDD	N / A	YES (eSATA)	
	Sensor In (NO, NC) Relay Out	N / A	Alarm-in x 16 Relay-out x 2	Alarm-in x 16 Relay-out x 4
	Serial Interface	RS-485		RS-485 x2
	USB 2.0 Ports	USB 3.0 x1, USB2.0 X2		
	Dimension (mm)	430(w)x55(h)x293(d)		442(w)x92(h)x438(d)
	Power Rating	12V 5A, 60W	12V 5.83A ,70W	AC 110/220V 250W
Display	Split Screen	1, 4, 9, 13, 16, SEQ.		
	Auto Channel Switching Mode	Switching time : 1 ~ 99 sec Zoom, Auto SEQ.		
Recording	Compression	H.264 High Profile		
	Main (Recording) Resolution	1920 x 1080, 1280 x 720; 944 x 480 .704 x 480, 352 x 240 (NTSC) / 944 x 576 ,704 x 576, 352 x 288 (PAL)		
	Sub (Network) Resolution	640 x 360 / 352 x 240, 176 x 120 (NTSC) / 352 x 288, 176 x 144 (PAL)		
	Picture Quality Mode	10~100 levels for adjustment Continuous, Event, Schedule		
	Record Rate	NTSC 1080p 240fps; 720p 480 fps		
		PAL 1080p 200fps ; 720p 400 fps		
	Pre-Alarm Post-Alarm	1 ~ 5 SEC 1 ~ 100 SEC		
Playback	Search Mode	Date / time, Event		
	Zoom	*Digital (x2 ~ x5)		
Network	Network Interface	10 / 100 Ethernet		
	Protocol	TCP / IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS		
	Application	Windows XP / VISTA/7, Mac OS X		
	Remote Software	SoCatch, IE Browser, iCMS Pro		
	Account	1 Admin + 10 Users		
Mobile Device	Windows Phone 7.8, iPhone, iPad, Android			
Backup	Interface	USB or SATA		
	Audio Backup	YES		
	Backup Type	Network, ext. USB flash device , SATA optical DVD..etc.		
Alarm	Motion Detection	Sensitivity : 100 levels for each channel Area : Programmable individually		
	Event Log	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)		
OSD & DVR Control	Multi-Language	Supported		
	Camera Title	Multi-Language		
	USB Mouse	YES		
	Touch Panel	Touch Panel LCD Monitor (USB Interface, EETI Chipset Only)		
	Remote Controller	IR Remote Control		
	System Upgrade	USB Flash Drive, iWatch DVR		
Pan / Tilt / Zoom Control	Control From RS485 Interface (Pelco P, Pelco D, Samsung, LG, LiLin)			
General	Operating Temperature	-10°C ~ +55°C (14°F ~ 131°F)		
	Operating Humidity	10%~80%		

All specifications are subject to change without notice.



TEL : 886-2-5550-6660 FAX : 886-2-5550-6670
2F, No. 26, Lane 513, Rueiguang Rd., Neihu District,
Taipei City 114, Taiwan



www.icatchinc.com